SAGOLA 430 PLUS



MINIAIRREGULATOR

SAGOLA 430 Plus

Mini Air Regulator

Air pressure regulator

- · Highly reliable air regulation system.
- Manufactured from a solid aluminium block.
- Diaphragm regulator from 0 to 10bar (145psi).
- · Quick release and short shift wheel.
- High quality analogue pressure gauge.
- Easy wall mounting.



Sagola 430 Plus

TECHNICAL SPECIFICATION	
Air Flow (at 7bar air inlet pressure)	1200 - 1700 I/min (60cfm)
Maximum Working Pressure	10bar (145psi)
Maximum Operating Temperature	90°C (194°F)
Dimensions (without coupling)	107 x 65 x 115 mm (4.21 x 2.56 x 4.53")
Weight	544g (19.19lbs)
Packing List	Sagola 430 Plus Mini Air Regulator

Part Numbers		³‰" Inlet	1⁄4" Inlet
Sagola 430 Plus Mini Air Regulator	PT10740501	PT10740502	PT10740503

SAGOLA 439 PLUS AIR FILTER

SAGOLA 439 Plus

Air Filter

High flow filter for insertion in air lines

- Semi-automatic draining system.
- · Minimum pressure loss.
- Suitable for all type of installations, accessories included.
- · Made in aluminium, high-durability.
- · Liquid residue check window.
- Minimum maintenance.



Sagola 439 Plus

TECHNICAL SPECIFICATION	
Air Flow (at 7bar air inlet pressure)	1700l/min (60cfm)
Maximum Working Pressure	10bar (145psi)
Maximum Operating Temperature	90°C (194°F)
Drain System	Semi-automatic
Dimensions (without coupling)	158 x 73 x 73 mm (6.22 x 2.87 x 2.87")
Weight	553g (19.51lbs)
Packing List	Sagola 439 Plus Air Purifier

Part Numbers		³⁄₅" Inlet	1/4" Inlet
Sagola 439 Plus Air Purifier	PT10720401	PT10720402	PT10720403

ACCESSORIES

Part Number	Description
PT53610204	40µm Porous Bronze Filter

SAGOLA 437 PLUS AIR LUBRICATOR



SAGOLA 437 Plus

Air Lubricator

Ideal for the proper lubrication of pneumatic tools.

- Safe operation from 3l/min.
- · Minimum flow restrictions.
- Multiple inlet and outlet dimensions (½", 3/8" and ½"). ft
- Oil level check window.
- Manual oil regulator by level check window, drop by drop system.
- · CNC machined in solid aluminium.
- Made in aluminium.
- · Minimum maintenance.



Sagola 437Plus

TECHNICAL SPECIFICATION	
Air Flow (at 7bar air inlet pressure)	1920l/min (67.8cfm)
Maximum Working Pressure	10bar (145psi)
Maximum Operating Temperature	90°C (194°F)
Dimensions (without coupling)	165 x 73 x 73 mm (6.49 x 2.87 x 2.87")
Weight	446g (15.73lbs)
Packing List	Sagola 437 Plus Air Lubricator

Part Numbers		¾" Inlet	1⁄4" Inlet
Sagola 437 Plus Air Lubricator	PT10710301	PT10710302	PT10710303

^{*} US-MIL, Euro-profile or NITTO version depending on part number ordered.

SAGOLA 479 PLUS PURIFIER REGULATOR



SAGOLA 479 Plus

Purifier Regulator

The most compact design for the small workshops, industry or air supplies to pneumatic tools.

- · Made in solid aluminium.
- · High air flow.
- Quality pressure gauge.
- · Highly reliable regulation system.
- Suitable for multiple hose sizes, couplings included.
- High filtering capacity with impurities check windows.
- · Semi-automatic draining system.



Sagola 479 Plus

TECHNICAL SPECIFICATION	
Air Flow (at 7bar air inlet pressure)	1700I/min (60cfm)
Maximum Working Pressure	10bar (145psi)
Maximum Operating Temperature	90°C (194°F)
Drain System	Semi-automatic
Dimensions (without coupling)	229 x 79 x 115mm (9.01 x 3.11 x 4.53")
Weight	886g (31.25lbs)
Packing List	Sagola 479 Plus Purifier Lubricator

Part Numbers	½" Inlet	¾" Inlet	1⁄4" Inlet
Sagola 479 Plus Purifier Regulator	PT10730401	PT10730402	PT10730403

ACCESSORIES

	··
Part Number	Description
PT53610204	40µm Porous Bronze Filter

^{*} US-MIL, Euro-profile or NITTO version depending on part number ordered.

S A G O L A 970 P L U S



PURFIFIER REGULATOR & LUBRICATOR

SAGOLA 970 Plus

Purifier-Regulator & Lubricator

Specially designed for the workshop, delivers clean air and lubricates all its tools.

- · Accurate control of the oil supply due to its manual drop by drop system.
- No pressure loss due to in-line design.
- Maximum reliability and productivity in with the minimum space.



Sagola 970 Plus

TECHNICAL SPECIFICATION	
Air Flow (at 7bar air inlet pressure)	1920I/min (67.8cfm)
Maximum Working Pressure	10bar (145psi)
Maximum Operating Temperature	90°C (194°F)
Drain System	Semi-automatic
Dimensions (without coupling)	229 x 148 x 115mm (9.01 x 5.83 x 4.53")
Weight	1450g (51.15lbs)
Packing List	Sagola 970 Plus Purifier-Regulator & Lubricator

Part Numbers	½" Inlet	³⁄₃" Inlet	½" Inlet
Sagola 970 Plus Purifier-Regulator & Lubricator	PT10750301	PT10750302	PT10750303

ACCESSORIES

Part Number	Description
PT53610204	40µm Porous Bronze Filter